DATASHEET

Type: **CONVEX**

Name: Wall light ID: US1357

Designed by:



Description

The Convex collection experiments with BROKISGLASS and makes use of its specific properties and processing methods. Designed and manufactured in the form of a convex lens, it pushes the boundaries of function, visual representation, and shaping of this unique and vibrant material. Together with a minimalist, precisely crafted body, it creates an unobtrusive yet unconventional luminaire. The utilitarian design, which highlights the beauty and optical properties of the glass, is well suited to a broad range of applications in both residential and commercial spaces. The Convex collection comprises a pendant and a wall light, each available in two sizes, whereas the wall variant can also be mounted on the ceiling. Choose from clear triplex opal, or a combination of clear triplex opal and grey triplex opal, where the darker fragments gradually transition to lighter towards the centre of the glass.




Tech. description

The light comprises a milled dural body with integrated LED module and balancing system and a mounting bracket. The Brokisglass shade is attached to the body of the light via bayonet system. The light is intended for installation on a wall or ceiling.

CONSTRUCTION SPECIFICATION

Weight:22 lbConstruction material:glass, metalCord length:86.6 inMounting:CeilingEnvironment:Dry

DIMENSIONS [in]



ELECTRICAL SPECIFICATION

 Input voltage [V]:
 100 - 240 V

 Freqvency [Hz]:
 50-60 Hz

 Max. power [W]:
 88 W

 Coverage IP:
 20

 Socket:

Light source: LED module

Energy class:

CERTIFICATIONS



DATASHEET LED SOURCE



CM17867 LED MODUL_D359_368LED_RA90/ 1CH_ _ 80W_CONVEX CV 2700K DNA

Type LED module

Lamp wattage [W] 75 W

Input voltage [V] 24 VDC

Energy class E

Flux [Im] 9983 Im

Light colour [K] 2700 K

CRI 90

Dimmable yes

CM17868 LED MODUL_D359_368LED_RA90/ 2CH_ 80W_CONVEX CV 2700K DNA

Type LED module

Lamp wattage [W] 75 W

Input voltage [V] 24 VDC

Energy class E


Flux [Im] 7430-11987 Im

Light colour [K] 18 CRI 90 Dimmable ve

1800-6500 K 90 yes



INNER FIXTURE



Drawing Hole placement

